

**SPC-0300SFPSF1, 300 ml. Polymix (bez stirena)****SPC-0420EXSSF1, 420 ml. Polymix Ultra (bez stirena)**

EXSSF

NEW

**FEATURES AND BENEFITS**

- Anchoring heavy and medium-load carrying attachments of threaded rods to concrete.
- All-weather bonding system for concrete.
- **Quick-cure formula.**
- **Base material temp.: -10°C to +29°C.**
- Dry, wet or flooded bore holes.
- Overhead installation allowed.
- Suitable for attachment points also close to the edge.
- Reaction to fire: Satisfy requirements for Class A1.
- Styrene free.
- **LEED certified for Green Building.**
- Colour: Grey
- Cartridge: 420ml

**BASE MATERIAL**

- Non-cracked concrete C 20/25 to C 50/60,
- Reinforced concrete,
- Unreinforced concrete

**APPLICATIONS**

- Barriers,
- Steel constructions,
- Handrails,
- Structural steel,
- Racking systems,
- Railings.



ETA-12/0450  
ETA-19/0324  
DoP 1343-CPR-M 626-1

**INSTALLATION TIME POLYMIX ULTRA**

Concrete temperature [°C]	Working time [min]	Min. curing time [min]
-10 ÷ -6	60	240
-5 ÷ -1	45	120
0 ÷ +4	25	80
+5 ÷ +9	10	45
+10 ÷ +14	4	25
+15 ÷ +19	3	20
+20 ÷ +29	2	15
Cartridge temperature	-5 ÷ +30 [°C]	