



# SDS- 3 PLUS SVRDLO ZA BETON



L1= ukupna dužina svrdla (mm)  
L2= radna dužina svrdla (mm)

| d   | vpc | L <sub>1</sub> | L <sub>2</sub> |
|-----|-----|----------------|----------------|
| 5   | 0   | 110            | 60             |
| 5   | 0   | 160            | 100            |
| 5   | 0   | 260            | 200            |
| 5   | 0   | 310            | 250            |
| 5   | 0   | 360            | 300            |
| 6   | 0   | 110            | 60             |
| 6   | 0   | 160            | 100            |
| 6   | 0   | 210            | 150            |
| 6   | 0   | 260            | 200            |
| 6   | 0   | 310            | 250            |
| 6.5 | 0   | 260            | 200            |
| 6.5 | 0   | 310            | 250            |
| 8   | 0   | 160            | 100            |
| 8   | 0   | 210            | 150            |
| 8   | 0   | 260            | 200            |
| 8   | 0   | 310            | 250            |
| 10  | 0   | 160            | 100            |
| 10  | 0   | 210            | 150            |
| 10  | 0   | 260            | 200            |
| 10  | 0   | 310            | 250            |
| 10  | 0   | 460            | 410            |
| 10  | 0   | 610            | 560            |
| 12  | 0   | 160            | 100            |
| 12  | 0   | 210            | 150            |
| 12  | 0   | 260            | 200            |
| 12  | 0   | 310            | 250            |
| 12  | 0   | 460            | 410            |
| 14  | 0   | 260            | 200            |
| 14  | 0   | 310            | 240            |
| 16  | 0   | 210            | 150            |
| 16  | 0   | 260            | 200            |
| 16  | 0   | 310            | 250            |
| 16  | 0   | 460            | 410            |
| 16  | 0   | 610            | 560            |



**RESISTANCE TO OVERHEATING**

The solid monocarbide tip, is inserted and brassed with copper, resistant to over 1000°C temperature raise

**HAMMERING EFFECT**

3x 135° edges, combine the most efficient drilling without cracking the concrete around

**PRECISION**

The self centering tip design, drives the bit straight

**TRAJECTORY CONTROL**

90°

**PERFECT HOLE, PERFECT ANCHORING**

hooster VS competitive drill bit

Answers to all world technical standards agreements

**BETTER DUST REMOVAL CAPACITIES**

hooster VS competitive drill bit

Its design offers the largest dust removal on its market

**SPECIAL REINFORCED CONCRETE**